

2020 HINO 268

GVW: 25,950 LBS. BBC: 108"
ENGINE MODEL: J08E-VB 260HP
660 LB-FT TORQUE (AVAILABLE)



TRUCKS

A Toyota Group Company



HINO INSIGHT CONNECTED VEHICLE



TELEMATICS, CASE MANAGEMENT, REMOTE DIAGNOSTICS...**STANDARD.**

At Hino we're changing the way we support our vehicles and customers so that your business is first. From the moment you take delivery of your Hino Insight equipped connected vehicle, you're on the road to more uptime and lower operating costs. Combining Telematics, Remote Diagnostics and Case Management in one integrated platform, Hino Insight puts critical vehicle and driver management tools at your fingertips.



WWW.HINO.COM

2020 HINO 268



| ENGINE | | |
|--------------------------------------|---|------------------|
| Model | STD Hino J08E-WU | OPT Hino J08E-VB |
| Max. output at 2,500 rpm (SAE Gross) | 230hp | 260hp |
| Max. torque at 1,500 rpm (SAE Gross) | 520 lb.-ft. | 660 lb.-ft. |
| Type | Diesel 4-cycle, 6 cylinder in-line, water-cooled, dry cylinder liners | |
| Fuel System | Common rail, direct injection type (Denso) | |
| Engine displacement | 8L | |
| Bore and Stroke | 4.41 x 5.12 in. | |

| WHEELS/TIRES/BRAKES | |
|---------------------|---|
| 6 Wheels | STD Steel 22.5X8.25 10-stud disc powder coated white OPT Powder coated gray, or Polished aluminum |
| 6 Tires | STD 11R22.5-14, Fr-Rib, Rr-All Season OPT 255/70R22.5-16, Fr-Rib, Rr-All Season OPT 295/75R22.5-14, Fr-Rib, Rr-All Season |
| Service brake | Hydraulic system with disc brake for front and rear wheels |
| Exhaust brake | Electric-pneumatic with valve in exhaust pipe |
| Parking brake | Lever control with cable, internal expanding drum type |

| FRAME | | |
|--|--------------------|------------|
| Ladder type | Straight C channel | |
| Width (in.) | 34 | |
| Yield strength (PSI) | 80,000 | |
| Resisting bending moment (one side, no reinforcement) in.-lbs. | 152" WB | All others |
| | 1,280,000 | 1,031,900 |

| AXLE/SUSPENSION | | |
|-----------------|--|--|
| Front axle | MFS-10 series reverse Elliot, "I" beam (oil lubricated) | |
| Front spring | Taper-leaf springs with shock absorbers | |
| Rear axle | MS19-14X, full floating, single reduction, single-speed, hypoid gearing | |
| Rear Suspension | STD Spring Semi-elliptic main OPT Air ride suspension - Hendrickson OPT Air ride suspension - dump valve (electric), single & dual valve | |

| WEIGHT CAPACITIES | | |
|----------------------|---------------|--|
| Front axle/susp lbs. | 10,000/12,000 | |
| Rear axle/susp lbs. | 19,000/19,000 | |

| CHASSIS EQUIPMENT | | |
|-------------------|---|--|
| Fuel Tank | STD 50 gallon OPT Dual 50 gal./Single 70 gal./Single 95 gal. | |
| DEF tank | 4.7 gal. | |

| POWERTRAIN AND PERFORMANCE | | | |
|----------------------------|-------|--|-------------|
| Transmission | Type | Allison Six speed automatic with Fuelsense 2.0 | |
| | Model | STD-2200HS | OPT-2200RDS |
| | 1st | 3.102 | |
| | 2nd | 1.811 | |
| | 3rd | 1.406 | |
| Ratios | 4th | 1 | |
| | 5th | 0.712 | |
| | 6th | 0.614 | |
| | Rev. | -4.492 | |
| GVW (lbs.) | | 25,950 | 25,950 |
| GCWR* (lbs.) | | 26,000 | 26,000 |

| DIMENSIONS/WEIGHTS | | | | | | | |
|----------------------------------|-------|-------|-------|--------|--------|--------|--------|
| Wheelbase (in.) | 152/G | 175/J | 187/L | 205/M | 217/P | 235/R | 253/T |
| Cab to axle (in.) | 84.6 | 107.6 | 119.6 | 137.6 | 149.6 | 167.6 | 185.6 |
| Rear overhang (in.) | 50 | 63 | 75 | 75 | 97 | 97 | 79 |
| Frame height at front axle (in.) | 37.0 | 36.8 | 36.8 | 36.8 | 36.8 | 36.8 | 36.8 |
| Frame height at rear axle (in.) | 40.5 | 40.5 | 40.6 | 40.6 | 40.7 | 40.7 | 40.4 |
| Std. chassis weight (lbs.) | 9,920 | 9,865 | 9,920 | 10,030 | 10,140 | 10,185 | 10,220 |

| ELECTRICAL EQUIPMENT | | |
|----------------------|--|--|
| Batteries | STD Two, parallel connection, 1200 CCA (GR 31) OPT Multiple two battery choices OPT Multiple Three battery choices | |
| Alternator | STD 12V, 130A, Delco (brush) OPT 12V, 135A (brushless)/180A (brush)/200A (brush) | |
| Starter | Denso-12V, 4.8kW | |

| WHY DRIVERS LOVE OUR TRUCKS | | |
|--------------------------------------|--|--|
| Bluetooth AM/FM radio with CD player | | |
| Air Ride drivers seat | | |
| Air conditioning | | |
| Cruise control | | |
| Tilt and telescopic steering wheel | | |
| 55 Degree wheel cut | | |
| 80 Degree door opening | | |
| 4007 sq. in. windshield area | | |
| Exterior grab handle | | |

| WHY OWNERS LOVE OUR TRUCKS | | |
|----------------------------|--|--|
| | | |
| | | |

| | |
|-----------------|--|
| ENGINE WARRANTY | STD - 5 years/250,000 miles OPT - 7 years/150,000 miles |
| HINOCARE | OPT - Preventive care extension |
| HINOWATCH | 24/7 Roadside Assistance |
| HINO INSIGHT | Telematics by Verizon Remote Diagnostics Case Management |
| | STD 1 Year OPT 3 & 5 Yr STD 5 Years STD 5 Years |

| POPULAR OPTIONAL EQUIPMENT (partial list) | | |
|---|--|--|
| Allison Fuel Sense Plus / Max | | |
| Anti-siphon device insert in fuel tank | | |
| Back-up alarm | | |
| Cab paint, exterior - custom (factory) | | |
| Engine idle shutdown | | |
| Exhaust system - vertical stack type | | |
| Mirrors, fender mounted-chrome (both sides or passenger only) | | |
| Mirrors, outside rearview-chrome | | |
| Mirrors-power heated (available in chrome) | | |
| Power windows and door locks (available with keyless entry) | | |
| Programmable speed limit 65,70 mph | | |
| Rear helper spring-sub leaf type | | |
| Stabilizer bar, rear (leaf suspension only) | | |
| Battery disconnect & jump start station | | |

All specifications of the products are with normal manufacturing allowances and tolerances. Hino Motors Sales, U.S.A., Inc. reserves the right to alter specifications at any time without previous notice. *Condition is city delivery and 8% max grades. ***24,200 lbs. when used in refuse application